



HOSHIZAKI

Product Catalogue - Version 4.0

STANDARD Refrigerators & Freezers



STANDARD Product Range

This range is made up of gastronorm 2/1 cabinets and 1/1 counters, available as a refrigerator or freezer with cabinets available in single and double and split doors and counters in double and triple doors.

- Carefully designed to ensure the optimal circulation of air at all times.
- Refrigerated air is circulated around the cabinet to maintain the storage of foodstuffs at the correct temperature using an energy efficient DC Fan.
- Exterior and interior are made of stainless steel. Counters have an inside door cover of grey ABS.
- Temperature ranges:
Cabinet: 0 to 16 & -25 to -7
Counter: -6 to 12 & -25 to -7
- These counters and cabinets offer great versatility as they can be used for different types of storage as requirements change or seasonal changes dictate menu variations.



Parts & Labour

Counters



Customer Benefits

- The stainless steel composition of the machine allows the worktop to double-up as a food preparation area, reducing the footprint of the machine in frequently space-restricted commercial environments.
- The compressor assembly can be easily accessed or removed from the machine, allowing easy maintenance and reducing costs.
- An energy efficient DC fan (80% more energy efficient than AC fan) considerably reduces the amount of energy consumed by the machine, reducing its impact on both the environment and your finances.

Cabinets



Customer Benefits

- An energy efficient DC fan (80% more energy efficient than AC fan) considerably reduces the amount of energy consumed.
- Routine cleaning and maintenance schedules are quick and easy to carry out, facilitated by the ergonomic design of the unit.
- Machines in this range include automatically closing doors (when an angle of less than 90 degrees). This reduces the risk of doors accidentally being left open, increasing the amount of energy consumed, and avoiding product spoil.
- The front frame of the freezer cabinet is heated, which when combined with the units efficient insulation, mean that condensation cannot build up on the exterior panels of the cabinet.
- The evaporator defrost cycle of the freezer is scheduled to run every six hours, maintaining energy efficiency by reducing the build up of ice on the evaporator.

These units are supplied with castors as standard allowing them to be easily moved when looking to relocate equipment, or for cleaning purposes. Legs are optional.



STANDARD Product Highlights



Easy Cleaning

Removable door gaskets for easy cleaning.



Adjustable Shelves

The counter offers one height-adjustable shelf per section as standard.



Hygienic Design

Dished stainless interior and base with rounded edges for easy cleaning.



User-Friendly Controller

Control panel with digital thermometer/thermostat for accurate control and easy reading. A transparent plastic cover protects against accidental adjustment of temperature and fluid spillage.



Easy Maintenance

Easy access to front loaded air filter for cleaning.



Easy Service

A compact slide out refrigeration unit for easy maintenance and service access.



Castors or legs

A choice between lockable castors and adjustable legs.

The leg height can be adjusted from 150 to 180mm.

RTE-120SNA - Refrigerator

Product Code	RTE-120SNA
Number of Shelves	2
Gross Capacity (L)	222
Temperature (°C)	-6 to 12
Exterior / Interior	Stainless (Galvanized - Rear/ Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1200 x 600 x 850 - 880 (With legs) 1200 x 600 x 815 (With castors)
Weight Gross / Net (kg)	86/77
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,28



FTE-120SNA - Freezer

Product Code	FTE-120SNA
Number of Shelves	2
Gross Capacity (L)	222
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/ Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1200 x 600 x 850 - 880 (With legs) 1200 x 600 x 815 (With castors)
Weight Gross / Net (kg)	90/81
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,66



RTE-150SNA - Refrigerator

Product Code	RTE-150SNA
Number of Shelves	2
Gross Capacity (L)	305
Temperature (°C)	-6 to 12
Exterior / Interior	Stainless (Galvanized - Rear/ Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1500 x 600 x 850 - 880 (With legs) 1500 x 600 x 815 (With castors)
Weight Gross / Net (kg)	99/89
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,29





STANDARD Counter Refrigerators & Freezers

www.hoshizaki-europe.com



FTE-150SNA - Freezer

Product Code	FTE-150SNA
Number of Shelves	2
Gross Capacity (L)	305
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1500 x 600 x 850 - 880 (With legs) 1500 x 600 x 815 (With castors)
Weight Gross / Net (kg)	102/92
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,66



RTE-180SNA - Refrigerator

Product Code	RTE-180SNA
Number of Shelves	3
Gross Capacity (L)	385
Temperature (°C)	-6 to 12
Exterior / Interior	Stainless (Galvanized - Rear/Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1800 x 600 x 850 - 880 (With legs) 1800 x 600 x 815 (With castors)
Weight Gross / Net (kg)	115/103
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,31



FTE-180SNA - Freezer

Product Code	FTE-180SNA
Number of Shelves	3
Gross Capacity (L)	385
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1800 x 600 x 850 - 880 (With legs) 1800 x 600 x 815 (With castors)
Weight Gross / Net (kg)	121/109
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,95

RTE-120SDA-GN 1/1 - Refrigerator

Product Code	RTE-120SDA-GN 1/1
Number of Shelves	2
Gross Capacity (L)	265
Temperature (°C)	-6 to 12
Exterior / Interior	Stainless (Galvanized - Rear/ Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1200 x 700 x 850 - 880 (With legs) 1200 x 700 x 815 (With castors)
Weight Gross / Net (kg)	93/83
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,28



FTE-120SDA-GN 1/1 - Freezer

Product Code	FTE-120SDA-GN 1/1
Number of Shelves	2
Gross Capacity (L)	265
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/ Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1200 x 700 x 850 - 880 (With legs) 1200 x 700 x 815 (With castors)
Weight Gross / Net (kg)	97/87
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,66



RTE-170SDA-GN 1/1 - Refrigerator

Product Code	RTE-170SDA-GN 1/1
Number of Shelves	3
Gross Capacity (L)	412
Temperature (°C)	-6 to 12
Exterior / Interior	Stainless (Galvanized - Rear/ Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1660 x 700 x 850 - 880 (With legs) 1660 x 700 x 815 (With castors)
Weight Gross / Net (kg)	115/103
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,30





STANDARD Counter Refrigerators & Freezers

www.hoshizaki-europe.com



FTE-170SDA-GN 1/1 - Freezer

Product Code	FTE-170SDA-GN 1/1
Number of Shelves	3
Gross Capacity (L)	412
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/Bottom)/Stainless, ABS Plastic
Dimensions W x D x H (mm)	1660 x 700 x 850 - 880 (With legs) 1660 x 700 x 815 (With castors)
Weight Gross / Net (kg)	121/109
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/220 - 240V/50Hz
Electrical Consumption (kW)	0,90

Available Optional Items:

Counters	Cabinets
Splash back tops (120/170)	Additional shelf (2/1)
Additional shelf (1/1)	Support rails
Shelf clips	Adjustable legs
Adjustable legs	



HRE-70B 2/1 - Refrigerator

Product Code	HRE-70B
Number of Shelves	4
Gross Capacity (L)	631
Temperature (°C)	0 to 16
Exterior / Interior	Stainless (Galvanized - Rear/Bottom) /Stainless
Dimensions W x D x H (mm)	700 x 850 x 2050 - 2080 (With legs) 700 x 850 x 2015 (With castors)
Weight Gross / Net (kg)	131/116
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/230V/50Hz
Electrical Consumption (kW)	0,348



HFE-70B 2/1 - Freezer

Product Code	HFE-70B
Number of Shelves	4
Gross Capacity (L)	631
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/Bottom) /Stainless
Dimensions W x D x H (mm)	700 x 8500 x 2050 - 2080 (With legs) 700 x 850 x 2015 (With castors)
Weight Gross / Net (kg)	131/116
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/230V/50Hz
Electrical Consumption (kW)	0,572





STANDARD Cabinet Refrigerators & Freezers

www.hoshizaki-europe.com



HRE-140B 2/1 - Refrigerator

Product Code	HRE-140B
Number of Shelves	8
Gross Capacity (L)	1379
Temperature (°C)	0 to 16
Exterior / Interior	Stainless (Galvanized - Rear/Bottom)/ Stainless
Dimensions W x D x H (mm)	1400 x 850 x 2050 - 2080 (With legs) 1400 x 850 x 2015 (With castors)
Weight Gross / Net (kg)	189/164
Insulation	Polyurethane Foam
Refrigerant	R134a
Electrical Supply	1/230V/50Hz
Electrical Consumption (kW)	0,501



HFE-140B 2/1 - Freezer

Product Code	HFE-140B
Number of Shelves	8
Gross Capacity (L)	1372
Temperature (°C)	-25 to -7
Exterior / Interior	Stainless (Galvanized - Rear/Bottom)/ Stainless
Dimensions W x D x H (mm)	1400 x 850 x 2050 - 2080 (With legs) 1400 x 850 x 2015 (With castors)
Weight Gross / Net (kg)	199/174
Insulation	Polyurethane Foam
Refrigerant	R404A
Electrical Supply	1/230V/50Hz
Electrical Consumption (kW)	0,723





HOSHIZAKI

Hoshizaki Europe B.V.

Tel. +31 20 6918499
Fax +31 20 6918768
sales@hoshizaki.nl

Hoshizaki UK (UK, Ireland)

Tel. +44 845 456 0585
Fax +44 132 283 8331
uksales@hoshizaki.co.uk

Hoshizaki Deutschland (Germany, Switzerland, Austria)

Tel. +49 2154/92810
Fax +49 2154/928128
info@hoshizaki.de

Hoshizaki France

Tel. +33 1 48 63 93 80
Fax +33 1 48 63 93 88
info@hoshizaki.fr

Hoshizaki Iberia (Spain, Portugal)

Tel. +34 93 478 09 52
Fax +34 93 478 08 00
info@hoshizaki.es

Hoshizaki Middle East

Tel. +971 48 876 612
Fax +971 48 876 613
sales@hoshizaki.ae

Hoshizaki Nederland & België

Tel. +31 20 5650420 (Nederland)
Tel. +32 2 712 30 30 (België)
Fax +31 20 6918768
sales@hoshizaki.nl (Nederland)
info@hoshizaki.be (België)

www.hoshizaki-europe.com

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hoshizaki Europe B.V. assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.